



SECTION

ELEVATION

NOTES:

1. ALL LUMBER SHALL BE D.F. #2 OR BETTER, PT ACQ/CBA, OR APPROVED EQUAL.
2. UNLESS OTHERWISE DIRECTED BY BELLEVUE PARKS, INSTALL DIAGONAL BRACE RAILING (4x4) AT ALL END AND CORNER SECTIONS WITH TOP OF BRACE AT TOP OF END SECTION/CORNER.
3. TOP CAP: SEEMS TO BE CUT AT 22.5°. EASE ALL EXPOSED EDGES 1/4" RADIUS. JOINTS TO BE ALTERNATED WITH 2x4 HORIZONTAL RAIL JOINTS.
4. GRIND BOLTS FLUSH WITH HEX NUT. TREAT EXPOSED ENDS WITH RUST PROTECTING GALV. PAINT.
5. 16'x5' HOG WIRE PANELS: 0.25" DIA. GALV. ROD WIRING WITH 2"x4" MESH OPENINGS.
6. THE HEIGHT BETWEEN FINISHED GRADE AND BOTTOM RAIL SHALL BE 6" WHENEVER POSSIBLE BUT MAY BE ADJUSTED AS NECESSARY ON SLOPED GRADES TO MAINTAIN LEVEL RAILS.



TITLE:  
**FENCE - BOARD WITH FABRIC - STANDARD**

DRAWING #:	PK-FE-04A
SCALE:	N.T.S.
REVISION DATE:	01-2019
DEPARTMENT:	PARKS